

# Alpha External Screen Awnings

## Quoting Best Practice

When deciding on where to fit your awning, there are a couple of things that need to be considered to ensure a successful installation. This includes checking for the following:

### Checklist

- Ensure there are no obstructions that could interfere with the installation and operation of the awning. Consider things such as light fittings, doors, spouting pipes, power lines, posts etc
- Select the right model for the customers' requirements
  - **Alpha Straight Drop**
  - **Alpha Cable Guide**
  - **Alpha STC**
  - **Alpha Pivot Arm**
  - **Alpha MagnaTrack**
- Measure width and drop of where the awning is to be installed
  - **If measuring for MagnaTrack, ensure both width measurements (top & bottom) and both drop measurements (left & right) are provided**
- Select awning Hardware Colour and Fabric Colour to be used
- Choose the right headbox requirement
  - **STC & MagnaTrack - recommended ordered with a Closed Headbox**
  - **Pivot Arm - Only available with Open Headbox or Open Roller**
- Add locking option either Hold Down Straps or Locking Bolts
  - **Note: Not available for MagnaTrack Awnings**
- Choose your operating option; either Crank Handle, Automation or Spring Operation (STC Only)
  - **If crank handle, select the length of handle required**
  - **If Awning is automated, select the motor required. You will need to ensure that you select the motor positioning ensuring there is power accessible to that side. Select remote control option**
  - **Note: MagnaTrack only available automated**
- Confirm control side, Mounting Type & Fabric roll direction
- MagnaTrack: Ensure you choose Keder Colour & whether the bottom rail is to be supplied attached to the awning or not
- Submit order