## **Evo External Screen Awnings**

## **Quoting Best Practice**

When deciding on where to fit your awning, there are a couple of things that need to be considered to ensure a successful installation. This includes checking for the following:

Checklist
-----------

Ensure there are no obstructions that could interfere with the installation and operation of the awning. Consider things such as light fittings, doors, spouting pipes, power lines, posts etc
Select the right model for the customers' requirements
Measure width and drop of where the awning is to be installed  o If measuring for MagnaTrack, ensure both width measurements (top & bottom) and both drop measurements (left & right) are provided
Select awning Hardware Colour and Fabric Colour to be used
Choose the right headbox requirement  o STC & MagnaTrack - recommended ordered with a Closed Headbox  Pivot Arm - Only available with Open Headbox or Open Roller
Add locking option either Hold Down Straps or Locking Bolts  o Note: Not available for MagnaTrack Awnings
Choose your operating option; either Crank Handle, Automation or Spring Operation (STC Only)  o If crank handle, select the length of handle required  o If Awning is automated, select the motor required. You will need to ensure that you select the motor positioning ensuring there is power accessible to that side. Select remote control option  Note: MagnaTrack only available automated
Confirm control side, Mounting Type & Fabric roll direction
MagnaTrack: Ensure you choose Keder Colour & whether the bottom rail is to be supplied attached to the awning or not
Submit order

